



Z.I.S. SPEZIALBAUSTOFFE

Composite cable conduits made of PE-HD with outer corrugation



### Standard design

Manufactured acc. to DIN EN 61386-24

**Type** with outer corrugation and inner pipe

**Type** 450 N

**Sleeve type** Double plug-in sleeve, sand-tight design

**Material** PE-HD

**Length** 6 m

**Colour Outer surface** black

### Possible designs

**Sleeve type** double plug-in sleeve, water-tight design

**Length** on request

**Colour** red, yellow, blue, green or orange

Item designation	Dimensions			Pallet contents (m)
	DN	$\varnothing d_i$ (mm)	$\varnothing d_a$ (mm)	
<b>VBR-S 50</b>	50	39 <sup>+1,5</sup>	50 <sup>+1,0</sup>	1170
<b>VBR-S 63</b>	63	50 <sup>+1,2</sup>	63 <sup>+1,2</sup>	612
<b>VBR-S 75</b>	75	61 <sup>+1,5</sup>	75 <sup>+1,4</sup>	978
<b>VBR-S 90</b>	90	74 <sup>+2,0</sup>	90 <sup>+1,7</sup>	648
<b>VBR-S 110</b>	110	93 <sup>+2,0</sup>	110 <sup>+2,0</sup>	402
<b>VBR-S 125</b>	125	107 <sup>+2,0</sup>	125 <sup>+2,3</sup>	306
<b>VBR-S 160</b>	160	138 <sup>+2,5</sup>	160 <sup>+2,3</sup>	198

Z.I.S. SPEZIALBAUSTOFFE GMBH

Karl-Rapp-Straße 1 · 92442 Wackersdorf · Germany  
 Tel.: +49 (0)94 31 / 797 99-0 · Fax: +49 (0)94 31 / 797 99-20  
 info@zis-spezialbaustoffe.de · www.zis-spezialbaustoffe.de



Wir sind Mitglied bei  
 der Gütegemeinschaft  
 Leitungstiefbau e.V.